

PUROIL 100 MP



FILTERCOMM



O L I O & T R U C C I O L I

TECHNICAL SHEET

	Units	PUROIL 100 MP
Motors Type		3 By-Pass
Power	kW-HP	3,9 - 5,2
Voltage Frequency	V Hz	230 50/60
Maximum vacuum	mBar	250
Maximum air flow	m³/h	570
Inlet	Ø mm	50
Noise level – (EN ISO 3744)	dB(A)	72
Liquid capacity	Lt	100
Solid capacity	Lt	50
Dimensions	mm	700X450
Height	mm	1400
Weight	Kg	90
Intake time	L/sec	100/26
Oil filter		Included
Filtration efficiency	µ	150
Media		Nylon
Discharge type		By gravity



PUROIL T 100



O L I O & T R U C T U R I C I O L I

TECHNICAL SHEET

	Units	Puroil T 100
Type		Side channel blower
Power	kW-HP	3 - 4
Voltage Frequency	V Hz	400 50/60
IP Insulation class		55 F
Maximum vacuum	mBar	320
Vacuum in continuous run	mBar	250
Maximum air flow	m³/h	420
Relief valve		Included
Inlet	Ø mm	50
Noise level – (EN ISO 3744)	dB(A)	78
Liquid capacity	Lt	100
Solid capacity	Lt	50
Dimensions	mm	840 X 710
Height	mm	1620
Weight	Kg	110
Intake time	L/sec	100/26
Discharge time	L/sec	100/92
Oil filter		Included
Discharge type		Reverse flow

